

PROJECT
STATUS
ORDER CODE
QUANTITY

HELIOS PIXEL LED NEON 24VDC

CLC/HELIOS PIXEL

FLEXIBLE NEON PIXEL RGB W/ IC REMOTE

RUN LENGTH UP TO 10 METER

ETL listed

Instant-on, no warm-up time, no transformer required, direct plug in 120vac.

High quality anti-corrosive PCB, Anti UV PVC, suitable for Indoor/ Outdoor.

High power efficient SMD5050 technology.

Suitable for indoor/outdoor use such as display lighting, building surrounds, architecture trace lines.



High brightness 60 LED's/M

Free of harmful mercury, environment friendly.

HELIOS PIXEL neon flex can provide rainbow effect color mixing.

SPECIFICATIONS

Voltage	24vdc
Wattage	12watts/M,
Lumens	26Lm/LED, 1320Lm /
PF	0.9
CRI	80
Cutting unit	7cm
Dimensions	8x16mm
IP rating	IP65
Lifetime	30,000 hrs
LED quantity	60 LED's/M
Light Source	SMD2835
PVC	Anti-UV- OPAL
Copper wire	100% copper 16x0.18 cm2
Max Length	100 Metre (10A rectifier)
Operating Temp	-15*C-40*C



Related products

AWIDE RANGE OF CONNECTORS AND MOUNTING EXTRUSIONS AVAILABLE

ASK YOUR SALES REP FOR DETAILS

NOTES

UNCOIL ENTIRE ROLL BEFORE PLUGGING IN

TO AVOID MELTING

INSTALL WITH LIGHTS POWERED OFF

COVE LIGHT APPLICATION, BEST TO INSTALL ON VERTICAL WALL SHINING INWARD.

WHICH IS EASIER FOR MOUNTING, KEEPS LIGHT ABOVE DUST, BETTER HEAT DISSIPATION AND PERFORMANCE.

DO NOT PUT TENSION ON CABLE CONNECTORS, USE CLIPS TO MOUNT CONNECTORS

WHEN BENDING LIGHT AROUND A CORNER DO NOT USE MOUNTING CLIP WITHIN 10" OF CORNER, THE IDEA IS TO LET THE LIGHT MAKE IT'S OWN GENTLE CURVE

DIMMING:

THIS PRODUCT IS FULLY DIMMABLE WITH TRIAC DIMMING.

TRIAC DIMMING IS THE MOST COMMON FORM OF DIMMING, ALSO KNOWN AS FORWARD PHASE, LEADING EDGE, SCR.

STAGE SHOWS WITH TOURING DIMMER RACKS;

LEPRECON RACKS ARE MOSTLY TRIAC, ETC SENSOR RACKS ARE MOSTLY REVERSE PHASE, SO REQUEST A TRIAC MODULE, EG D20 OR AD20.